



WILDCAT POWER GEN

PROVIDING BETTER POWER

SENTINEL DIESEL: 60KW

The UL2200 listed Sentinel generator was designed with rugged simplicity in mind. Three phase, open skid or enclosed packages designed for emergency applications but built to run for extended power outage periods of time on prime rated liquid cooled engine platforms.



Durable Industrial Engine

- Usually reserved for industrial applications, the Sentinel's power plant is a premier industrial fixed speed (1,800 RPM) engine built to provide strong, reliable power without giving up quiet operation and engine longevity.

Quality Clean Power

- Voltage regulation ensures that electronics are safely powered with less 5% total harmonic distortion (THD) at no load.

NFPA-110

- Wildcat designed the Sentinel to exceed NFPA-110, Level 2 Emergency Power Supply Systems (EPSS) by providing prime power (PP) to meet EPSS Class 168 Type 10.

Digital Controls

- Designed for single genset applications, the Sentinel's digital controls monitor the genset's voltage, current, power, frequency, engine speed, oil pressure and coolant temperature on a back-lit LCD display for ease of use.

Industrial Class Alternator

- Protected with Class H insulation and standard 40°C nominal rating, the Sentinel's standard 12-wire winding and 2/3 pitch meet all key international standards and regulations including UL 1446.

Easy to Service

- Preventative maintenance and in-field repairs are made easier with our simplified engineering and non-proprietary parts.

GENERATOR SET RATING

Model	Voltage	Power Factor	Phase	Hertz	Circuit Breaker Amps	kW / kVA	BMEP (Bar)	BSFC (g/hp*hr)	Emission Compliance	Controller
Sentinel Diesel 49KW SE0060D3ASXE	120 / 240	1.0	1	60	250	49 / 49	14.6	162	Tier 3	DeepSea
Sentinel Diesel 60KW SE0060D3BSXE	208 / 110	0.8	3	60	225	60 / 75	14.6	162	Tier 3	DeepSea
Sentinel Diesel 60KW SE0060D3CSXE	240 / 120	0.8	3	60	200	60 / 75	14.6	162	Tier 3	DeepSea
Sentinel Diesel 60KW SE0060D3DSXE	480 / 277	0.8	3	60	100	60 / 75	14.6	162	Tier 3	DeepSea



WILDCAT
POWER GEN

PROVIDING
BETTER POWER

SENTINEL

ENGINE SPECIFICATIONS

Engine

Manufacturer	KOEL
Type	4R810TA1 Powertrain 4 Cycle, Turbo Charged & Charge Air Cooled
Speed (RPM)	1800
Cylinder Arrangement	Inline 4
Displacement (L / cc)	3.2L / 3240cc
Bore & Stroke (in / mm)	3.779" x 4.409" / 96 x 112
Compression Ratio	16.5:1
Governor Type	Electronic
Frequency Regulation Steady State	+/- 0.25%
Frequency Regulation No-load to Full-load	Isochronous, Constant Speed
Air Filter Type	Dry
Limited Warranty	3 Years, 5,000 Hours

Lubrication System

Type	Full Pressure
Oil Capacity (qt / L)	12qt / 11.5 L
Oil Filter (Quantity / Type)	1/Spin-On

Cooling System

Radiator Type	Aluminum
Fan Type	Pusher

Sound Rating at 7 Meters, Lowest Side

No Load	72 dB(A)
---------	----------

Engine Crankcase Vent System

Engine Crankcase Vent System	Closed Crankcase Vent
------------------------------	-----------------------

Electrical System

Battery Quantity	1
Battery Voltage (VDC)	12
Battery CCA (A)	900
Battery Charging Alternator	
Ground (Negative/Positive)	Negative
Voltage (VDC)	12
Amperage (A)	32
Starter Motor Voltage (VDC)	12

Exhaust System

Exhaust Manifold Type	Dry
Exhaust Flow at Rated Load (gal/hr)	95.1
Exhaust Temperature at Rated Load (°F / °C)	1256 / 680
Maximum Allowable Back Pressure (in Hg / kPa)	2.95 / 10.0±1.0

Fuel System

Fuel Type	Ultra-Low Sulfur Diesel
Fuel Injection Pump	Mechanical Fuel Inline Pump
Fuel Filter	0.6 liter Single bowl Spin-on
Ignition System	Direct Injection

Fuel Consumption

Full Load:	4.94 GAL / HR
50% Load:	2.51 GAL / HR
No Load:	1.00 GAL / HR

STANDARD CONTROLLER



WILDCAT POWER GEN DeepSea Controller

- User-friendly control panel for troubleshooting
- Conveniently monitors diagnostic conditions, displays system fault codes and sets weekly exercise cycle
- Easy-to-read alpha-numeric scrolling display
- Single & 3 Phase generator applications
- UL recognized

Engine Output Deratings

Rated Temperature (°F / °C)	77 / 25
Rated Altitude	328 ft (100 m) Above Sea Level
Temperature Derate	1.5% for Each 10°F (5.6°C) Above Rated Temperature
Altitude Derate	2.5% for Each 1000 ft (305 m) Above Rated Altitude



WILDCAT
POWER GEN

PROVIDING
BETTER POWER

SENTINEL

ALTERNATOR SPECIFICATIONS

	Sentinel 49KW Single Phase Tier 3	Sentinel 60KW 3-Phase Tier 3	Sentinel 60KW 3-Phase Tier 3	Sentinel 60KW 3-Phase Tier 3
Model	SE0060D3ASXE	SE0060D3BSXE	SE0060D3CSXE	SE0060D3DSXE
Alternator Model	UCI224F	UCI224F	UCI224F	UCI224F
Manufacturer	Stamford	Stamford	Stamford	Stamford
Type	Brushless, 12-Lead	Brushless, 12-Lead	Brushless, 12-Lead	Brushless, 12-Lead
Frequency (Hz)	60	60	60	60
Phase	1	3	3	3
Winding Configuration	Double Delta	Parallel Star	Series Delta	Series Star
Exciter Type	Self Exciter	Self Exciter	Self Exciter	Self Exciter
Number of Poles	4	4	4	4
Voltage Regulator	MX341UL	MX341UL	MX341UL	MX341UL
Insulation Rating	Class H	Class H	Class H	Class H
Designed Temperature Rise Limit	125 °C	125 °C	125 °C	125 °C
Bearing (Quantity / Type)	1/Sealed	1/Sealed	1/Sealed	1/Sealed
Coupling	Flexible Disk	Flexible Disk	Flexible Disk	Flexible Disk
Amortisseur Windings	Full	Full	Full	Full
Voltage Regulation, NL to FL	+/- 1.0%	+/- 1.0%	+/- 1.0%	+/- 1.0%
One Step Load Acceptance	100% of Rating	100% of Rating	100% of Rating	100% of Rating
Total Harmonic Distortion (THD), NL to FL	<5%	<5%	<5%	<5%

- Complete winding protection for non-harsh environment with relative humidity ≤95%. IP23 Protection
- Manufactured according to the following standards: ISO 3046, ISO 8528-1, ISO 8528-3, ISO 8528-5, IEC 60034-1, BS 5000-3

Weight & Dimensions

Assembled Weight (lbs / kg) 3353 LBS / 1512 KG

Overall Dimensions (in / mm) 108.78" L x 41.78" W x 71.34" H 2763mm L x 1061mm W x 1812mm H

Need help? Visit wildcatpowergen.com

Complete the web form and a local dealer will contact you to answer questions on our generators and accessories.

620-500-5111

**Never Lose Power Again
With Wildcat Power Gen**